armex

from FENCEPOINT

DATASHEET

ARMEX 868 TWIN MESH

KEY FEATURES

- **Pre-Galvanised Steel** to BS 10346 (Ensures compliance to latest standards)
- **Cost Effective** (Long lasting physical protection)
- **Strength & Resilience** (High quality galvanised steel construction, rust resistant)
- **Versatility & Easy Installation** (Easy to install)
- **Security** (Anti-cut-through Panels)

SUITABLE FOR

- **Perimeter Fencing**
- **Boundary Demarcation**
- **Schools**
- **Industrial Estates**
- **Logistics Hubs**



Anti-Cut
Heay duty Twin Wire prevents easy cutting.

Wide range of heights
Available in 1.8 – 3.0m to suit many applications

Weather and damage resilient
Manufactured from pre-galvanised steel, the zinc coating helps prevent rust & corrosion. Powder coated as standard for extra resilience.

Visual appeal
Aesthetically pleasing and works well for Schools & Site Perimeters.

Your trusted partner for reliable, high-quality fencing solutions

armex from FENCEPOINT

FENCING SPECIFICATIONS

ARMEX 868 TWIN MESH

Panel Finished Height (weight)		1830mm (33.7kg), 2030mm (kg), 2430mm (44.8kg), 3030mm (55.9kg)
Panel Width		2515mm
Wire Diameter		8 x 6 x 8mm
Mesh Opening Dimension		50 x 200mm
Coating (product marked)		Pre-galvanised, nano coated & electrostatic powder coat
Colours available		Green (RAL6005), Black (RAL9005), others available on request
Clamp Bar System	**Intermediate Posts, dig-in (weight)**	60x40mm SHS, 2400mm (5.84kg) 2600mm (6.3kg), 3000mm (8.92kg) (80x60mm SHS) 3600mm (14kg)
	Corner Posts size, dig-in (weight)	60x40mm SHS, 2400mm (5.95kg), 2600mm (6.64kg), 3000mm (8.04kg) (80x60mm SHS) 3600mm (14kg)
	Clamp Bar Mesh Fixing (weight)	(40mm x 5mm), 1800mm (4.6 kg), 2000mm (4.87 kg), 2400mm (6 kg), 3000mm (7 kg)
	Clamp Bar Fixing Bolts	M8 x 120mm, Cup square bolts & shear nuts, Corrosion Resistant, Quantity per post:
	Post Thickness	2mm (hollow box frame)
Clip System	**Intermediate Posts, dig-in (weight)**	(60x60mm SHS) 2400mmc(8.9 kg), 2600mm (9.7 kg), 3000mm (11.10kg), 3600mm (kg)
	Corner Posts size, dig-in (weight)	(60x60mm SHS) 2400mmc(9 kg), 2600mm (9.8 kg), 3000mm, (11.15 kg), 3600mm (kg)
	Mesh Fixing Clips	38x30x10mm, 3mm thick, (Colours: black & green) Quantity per post:
	Fixing Bolts	M8 x 40mm, SQ Drive Hardened Steel Machine Screw, Corrosion Resistant Magni 565 Qty per post:
	Post Thickness	2mm (hollow box frame)

Fence Height	Intermediate	Corner
1.8m	9	18
2.0m	11	22
2.4m	13	26
3.0m	15	30

Fence Height	Intermediate	Corner
1.8m	5	10
2.0m	5	10
2.4m	6	12
3.0m	7	14

Fence Height	Intermediate	Corner
1.8m	5	10
2.0m	5	10
2.4m	6	12
3.0m	7	14

Fencepoint, Unit 35, Midfield Drive, Kirkcaldy KY1 3LW
T: 01592 772 455 **E:** sales@fencepoint.com